


Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration			Part Number
--------------	-------------	--------------	--------------------------------	--	--	-------------

Pushbutton_KJRT (Charcoal Bezel)



IP65



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Momentary/Spring Return

Red	-	1NO	-	-	GS1 KJRT-10-RT
Green	-	1NO	-	-	GS1 KJRT-10-GN
Yellow	-	1NO	-	-	GS1 KJRT-10-GB
Blue	-	1NO	-	-	GS1 KJRT-10-BL
Clear	-	1NO	-	-	GS1 KJRT-10-KL

1NC Momentary/Spring Return

Red	-	-	1NC	-	GS1 KJRT-01-RT
Green	-	-	1NC	-	GS1 KJRT-01-GN
Yellow	-	-	1NC	-	GS1 KJRT-01-GB
Blue	-	-	1NC	-	GS1 KJRT-01-BL
Clear	-	-	1NC	-	GS1 KJRT-01-KL

1NO 1NC Momentary/Spring Return

Red	-	-	-	1NO 1NC	GS1 KJRT-11-RT
Green	-	-	-	1NO 1NC	GS1 KJRT-11-GN
Yellow	-	-	-	1NO 1NC	GS1 KJRT-11-GB
Blue	-	-	-	1NO 1NC	GS1 KJRT-11-BL
Clear	-	-	-	1NO 1NC	GS1 KJRT-11-KL

2NO 2NC Momentary/Spring Return


Red	-	-	-	2NO 2NC	GS1 KJRT-22-RT
Green	-	-	-	2NO 2NC	GS1 KJRT-22-GN
Yellow	-	-	-	2NO 2NC	GS1 KJRT-22-GB
Blue	-	-	-	2NO 2NC	GS1 KJRT-22-BL
Clear	-	-	-	2NO 2NC	GS1 KJRT-22-KL

Pushbutton_KJRT (Charcoal Bezel)



IP65



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Maintained/Latching

Red	-	1NO	-	-	GS1 KJRT-10Z-RT
Green	-	1NO	-	-	GS1 KJRT-10Z-GN
Yellow	-	1NO	-	-	GS1 KJRT-10Z-GB
Blue	-	1NO	-	-	GS1 KJRT-10Z-BL
Clear	-	1NO	-	-	GS1 KJRT-10Z-KL

1NC Maintained/Latching

Red	-	-	1NC	-	GS1 KJRT-01Z-RT
Green	-	-	1NC	-	GS1 KJRT-01Z-GN
Yellow	-	-	1NC	-	GS1 KJRT-01Z-GB
Blue	-	-	1NC	-	GS1 KJRT-01Z-BL
Clear	-	-	1NC	-	GS1 KJRT-01Z-KL

1NO 1NC Maintained/Latching

Red	-	-	-	1NO 1NC	GS1 KJRT-11Z-RT
Green	-	-	-	1NO 1NC	GS1 KJRT-11Z-GN
Yellow	-	-	-	1NO 1NC	GS1 KJRT-11Z-GB
Blue	-	-	-	1NO 1NC	GS1 KJRT-11Z-BL
Clear	-	-	-	1NO 1NC	GS1 KJRT-11Z-KL

2NO 2NC Maintained/Latching

Red	-	-	-	2NO 2NC	GS1 KJRT-22Z-RT
Green	-	-	-	2NO 2NC	GS1 KJRT-22Z-GN
Yellow	-	-	-	2NO 2NC	GS1 KJRT-22Z-GB
Blue	-	-	-	2NO 2NC	GS1 KJRT-22Z-BL
Clear	-	-	-	2NO 2NC	GS1 KJRT-22Z-KL


Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration	Part Number
--------------	-------------	--------------	--------------------------------	-------------

Illuminated Pushbutton_KJRT (Charcoal Bezel)



IP65



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Momentary/Spring Return - 24V

Red	24V	1NO	-	-	GS1 KJRT-10-24-RT
Green	24V	1NO	-	-	GS1 KJRT-10-24-GN
Yellow	24V	1NO	-	-	GS1 KJRT-10-24-GB
Blue	24V	1NO	-	-	GS1 KJRT-10-24-BL
Clear	24V	1NO	-	-	GS1 KJRT-10-24-KL

1NC Momentary/Spring Return - 24V

Red	24V	-	1NC	-	GS1 KJRT-01-24-RT
Green	24V	-	1NC	-	GS1 KJRT-01-24-GN
Yellow	24V	-	1NC	-	GS1 KJRT-01-24-GB
Blue	24V	-	1NC	-	GS1 KJRT-01-24-BL
Clear	24V	-	1NC	-	GS1 KJRT-01-24-KL

1NO 1NC Momentary/Spring Return - 24V

Red	24V	-	-	1NO 1NC	GS1 KJRT-11-24-RT
Green	24V	-	-	1NO 1NC	GS1 KJRT-11-24-GN
Yellow	24V	-	-	1NO 1NC	GS1 KJRT-11-24-GB
Blue	24V	-	-	1NO 1NC	GS1 KJRT-11-24-BL
Clear	24V	-	-	1NO 1NC	GS1 KJRT-11-24-KL

2NO 2NC Momentary/Spring Return - 24V


Red	24V	-	-	2NO 2NC	GS1 KJRT-22-24-RT
Green	24V	-	-	2NO 2NC	GS1 KJRT-22-24-GN
Yellow	24V	-	-	2NO 2NC	GS1 KJRT-22-24-GB
Blue	24V	-	-	2NO 2NC	GS1 KJRT-22-24-BL
Clear	24V	-	-	2NO 2NC	GS1 KJRT-22-24-KL

Illuminated Pushbutton_KJRT (Charcoal Bezel)



IP65



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Maintained/Latching - 24V

Red	24V	1NO	-	-	GS1 KJRT-10Z-24-RT
Green	24V	1NO	-	-	GS1 KJRT-10Z-24-GN
Yellow	24V	1NO	-	-	GS1 KJRT-10Z-24-GB
Blue	24V	1NO	-	-	GS1 KJRT-10Z-24-BL
Clear	24V	1NO	-	-	GS1 KJRT-10Z-24-KL

1NC Maintained/Latching - 24V

Red	24V	-	1NC	-	GS1 KJRT-01Z-24-RT
Green	24V	-	1NC	-	GS1 KJRT-01Z-24-GN
Yellow	24V	-	1NC	-	GS1 KJRT-01Z-24-GB
Blue	24V	-	1NC	-	GS1 KJRT-01Z-24-BL
Clear	24V	-	1NC	-	GS1 KJRT-01Z-24-KL

1NO 1NC Maintained/Latching - 24V

Red	24V	-	-	1NO 1NC	GS1 KJRT-11Z-24-RT
Green	24V	-	-	1NO 1NC	GS1 KJRT-11Z-24-GN
Yellow	24V	-	-	1NO 1NC	GS1 KJRT-11Z-24-GB
Blue	24V	-	-	1NO 1NC	GS1 KJRT-11Z-24-BL
Clear	24V	-	-	1NO 1NC	GS1 KJRT-11Z-24-KL

2NO 2NC Maintained/Latching - 24V

Red	24V	-	-	2NO 2NC	GS1 KJRT-22Z-24-RT
Green	24V	-	-	2NO 2NC	GS1 KJRT-22Z-24-GN
Yellow	24V	-	-	2NO 2NC	GS1 KJRT-22Z-24-GB
Blue	24V	-	-	2NO 2NC	GS1 KJRT-22Z-24-BL
Clear	24V	-	-	2NO 2NC	GS1 KJRT-22Z-24-KL

Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration		Part Number
--------------	-------------	--------------	--------------------------------	--	-------------

Illuminated Pushbutton_KJRT (Charcoal Bezel)


IP65





3mm



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Momentary/Spring Return - 230V

Red	230V	1NO	-	-	GS1 KJRT-10-220-RT
Green	230V	1NO	-	-	GS1 KJRT-10-220-GN
Yellow	230V	1NO	-	-	GS1 KJRT-10-220-GB
Blue	230V	1NO	-	-	GS1 KJRT-10-220-BL
Clear	230V	1NO	-	-	GS1 KJRT-10-220-KL

1NC Momentary/Spring Return - 230V

Red	230V	-	1NC	-	GS1 KJRT-01-220-RT
Green	230V	-	1NC	-	GS1 KJRT-01-220-GN
Yellow	230V	-	1NC	-	GS1 KJRT-01-220-GB
Blue	230V	-	1NC	-	GS1 KJRT-01-220-BL
Clear	230V	-	1NC	-	GS1 KJRT-01-220-KL

1NO 1NC Momentary/Spring Return - 230V

Red	230V	-	-	1NO 1NC	GS1 KJRT-11-220-RT
Green	230V	-	-	1NO 1NC	GS1 KJRT-11-220-GN
Yellow	230V	-	-	1NO 1NC	GS1 KJRT-11-220-GB
Blue	230V	-	-	1NO 1NC	GS1 KJRT-11-220-BL
Clear	230V	-	-	1NO 1NC	GS1 KJRT-11-220-KL

2NO 2NC Momentary/Spring Return - 230V

Red	230V	-	-	2NO 2NC	GS1 KJRT-22-220-RT
Green	230V	-	-	2NO 2NC	GS1 KJRT-22-220-GN
Yellow	230V	-	-	2NO 2NC	GS1 KJRT-22-220-GB
Blue	230V	-	-	2NO 2NC	GS1 KJRT-22-220-BL
Clear	230V	-	-	2NO 2NC	GS1 KJRT-22-220-KL

Illuminated Pushbutton_KJRT (Charcoal Bezel)


IP65





3mm



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Maintained/Latching - 230V

Red	230V	1NO	-	-	GS1 KJRT-10Z-220-RT
Green	230V	1NO	-	-	GS1 KJRT-10Z-220-GN
Yellow	230V	1NO	-	-	GS1 KJRT-10Z-220-GB
Blue	230V	1NO	-	-	GS1 KJRT-10Z-220-BL
Clear	230V	1NO	-	-	GS1 KJRT-10Z-220-KL

1NC Maintained/Latching - 230V

Red	230V	-	1NC	-	GS1 KJRT-01Z-220-RT
Green	230V	-	1NC	-	GS1 KJRT-01Z-220-GN
Yellow	230V	-	1NC	-	GS1 KJRT-01Z-220-GB
Blue	230V	-	1NC	-	GS1 KJRT-01Z-220-BL
Clear	230V	-	1NC	-	GS1 KJRT-01Z-220-KL

1NO 1NC Maintained/Latching - 230V

Red	230V	-	-	1NO 1NC	GS1 KJRT-11Z-220-RT
Green	230V	-	-	1NO 1NC	GS1 KJRT-11Z-220-GN
Yellow	230V	-	-	1NO 1NC	GS1 KJRT-11Z-220-GB
Blue	230V	-	-	1NO 1NC	GS1 KJRT-11Z-220-BL
Clear	230V	-	-	1NO 1NC	GS1 KJRT-11Z-220-KL

2NO 2NC Maintained/Latching - 230V


Red	230V	-	-	2NO 2NC	GS1 KJRT-22Z-220-RT
Green	230V	-	-	2NO 2NC	GS1 KJRT-22Z-220-GN
Yellow	230V	-	-	2NO 2NC	GS1 KJRT-22Z-220-GB
Blue	230V	-	-	2NO 2NC	GS1 KJRT-22Z-220-BL
Clear	230V	-	-	2NO 2NC	GS1 KJRT-22Z-220-KL

Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration			Part Number
--------------	-------------	--------------	--------------------------------	--	--	-------------



Pilot Light_KJRN (Charcoal Bezel)



Dimensional Drawing:



Cut-out Hole Drawing:



24V

Red	24V	-	-	-	GS1 KJRN-24-RT
Green	24V	-	-	-	GS1 KJRN-24-GN
Yellow	24V	-	-	-	GS1 KJRN-24-GB
Blue	24V	-	-	-	GS1 KJRN-24-BL
Clear	24V	-	-	-	GS1 KJRN-24-KL

230V

Red	230V	-	-	-	GS1 KJRN-220-RT
Green	230V	-	-	-	GS1 KJRN-220-GN
Yellow	230V	-	-	-	GS1 KJRN-220-GB
Blue	230V	-	-	-	GS1 KJRN-220-BL
Clear	230V	-	-	-	GS1 KJRN-220-KL

Technical Specification

General Data:

Front Dimensions:	Ø 36 mm	Max. Storage Temperature:	-50°C ... 85°C
Panel Cut -out:	Ø 30.5 mm	Max. Operating Temperature:	-50°C ... 85°C, without illumination
Front Bezel Height:	2.7 mm		-30°C ... 65°C, using LEDs
Operating Travel:	6 mm	Mechanical Life:	1 m switching cycles
IP Rating:	IP67	Electrical Life:	1 m operations at rated load
Illumination:	Yes	Contact Resistance NO:	<20 mOhm
Contact Type:	Mod ular Contact Block	Contact Resistance NC:	<20 mOhm
Protection Class:	II (protective insulation)	Min. Current:	1 mA
Connection Type:	Screw Conne ction 2 x 2.5 mm ²	Min. Voltage:	5V
Contact Material:	AgNi		

	Alternate Current	Direct Current
Rated Insulation Voltage:	600V	600V
Rated Operating Voltage:	240V / 440V	440V / 250V / 125V / 60V / 24V
Rated Operating Current:	3A / 1.6A	0.12A / 0.2A / 0.4A / 1A / 2A

Approvals:



Use & Applications:


- ✓ The actuators are designed for exclusive applications as well as use in harsh environments.
- ✓ Flexible contact configuration and ease of assembly.
- ✓ The units can be used in every field of application.
- ✓ The control units are designed to accept a clearly visible marking, easy to produce and comprising a variety fo symbols and inscriptions.
- ✓ Multiple standards nameplates are available and also according to user's requirements.

Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration	Part Number
--------------	-------------	--------------	--------------------------------	-------------



Pushbutton_KJRMT (Silver Bezel)



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Momentary/Spring Return

Red	-	1NO	-	-	GS1 KJRMT-10-RT
Green	-	1NO	-	-	GS1 KJRMT-10-GN
Yellow	-	1NO	-	-	GS1 KJRMT-10-GB
Blue	-	1NO	-	-	GS1 KJRMT-10-BL
Clear	-	1NO	-	-	GS1 KJRMT-10-KL

1NC Momentary/Spring Return

Red	-	-	1NC	-	GS1 KJRMT-01-RT
Green	-	-	1NC	-	GS1 KJRMT-01-GN
Yellow	-	-	1NC	-	GS1 KJRMT-01-GB
Blue	-	-	1NC	-	GS1 KJRMT-01-BL
Clear	-	-	1NC	-	GS1 KJRMT-01-KL

1NO 1NC Momentary/Spring Return

Red	-	-	-	1NO 1NC	GS1 KJRMT-11-RT
Green	-	-	-	1NO 1NC	GS1 KJRMT-11-GN
Yellow	-	-	-	1NO 1NC	GS1 KJRMT-11-GB
Blue	-	-	-	1NO 1NC	GS1 KJRMT-11-BL
Clear	-	-	-	1NO 1NC	GS1 KJRMT-11-KL


2NO 2NC Momentary/Spring Return

Red	-	-	-	2NO 2NC	GS1 KJRMT-22-RT
Green	-	-	-	2NO 2NC	GS1 KJRMT-22-GN
Yellow	-	-	-	2NO 2NC	GS1 KJRMT-22-GB
Blue	-	-	-	2NO 2NC	GS1 KJRMT-22-BL
Clear	-	-	-	2NO 2NC	GS1 KJRMT-22-KL



Pushbutton_KJRMT (Silver Bezel)



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Maintained/Latching

Red	-	1NO	-	-	GS1 KJRMT-10Z-RT
Green	-	1NO	-	-	GS1 KJRMT-10Z-GN
Yellow	-	1NO	-	-	GS1 KJRMT-10Z-GB
Blue	-	1NO	-	-	GS1 KJRMT-10Z-BL
Clear	-	1NO	-	-	GS1 KJRMT-10Z-KL

1NC Maintained/Latching

Red	-	-	1NC	-	GS1 KJRMT-01Z-RT
Green	-	-	1NC	-	GS1 KJRMT-01Z-GN
Yellow	-	-	1NC	-	GS1 KJRMT-01Z-GB
Blue	-	-	1NC	-	GS1 KJRMT-01Z-BL
Clear	-	-	1NC	-	GS1 KJRMT-01Z-KL

1NO 1NC Maintained/Latching

Red	-	-	-	1NO 1NC	GS1 KJRMT-11Z-RT
Green	-	-	-	1NO 1NC	GS1 KJRMT-11Z-GN
Yellow	-	-	-	1NO 1NC	GS1 KJRMT-11Z-GB
Blue	-	-	-	1NO 1NC	GS1 KJRMT-11Z-BL
Clear	-	-	-	1NO 1NC	GS1 KJRMT-11Z-KL

2NO 2NC Maintained/Latching

Red	-	-	-	2NO 2NC	GS1 KJRMT-22Z-RT
Green	-	-	-	2NO 2NC	GS1 KJRMT-22Z-GN
Yellow	-	-	-	2NO 2NC	GS1 KJRMT-22Z-GB
Blue	-	-	-	2NO 2NC	GS1 KJRMT-22Z-BL
Clear	-	-	-	2NO 2NC	GS1 KJRMT-22Z-KL


Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration	Part Number
--------------	-------------	--------------	--------------------------------	-------------

Illuminated Pushbutton_KJRMT (Silver Bezel)



IP65



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Momentary/Spring Return - 24V

Red	24V	1NO	-	-	GS1 KJRMT-10-24-RT
Green	24V	1NO	-	-	GS1 KJRMT-10-24-GN
Yellow	24V	1NO	-	-	GS1 KJRMT-10-24-GB
Blue	24V	1NO	-	-	GS1 KJRMT-10-24-BL
Clear	24V	1NO	-	-	GS1 KJRMT-10-24-KL

1NC Momentary/Spring Return - 24V

Red	24V	-	1NC	-	GS1 KJRMT-01-24-RT
Green	24V	-	1NC	-	GS1 KJRMT-01-24-GN
Yellow	24V	-	1NC	-	GS1 KJRMT-01-24-GB
Blue	24V	-	1NC	-	GS1 KJRMT-01-24-BL
Clear	24V	-	1NC	-	GS1 KJRMT-01-24-KL

1NO 1NC Momentary/Spring Return - 24V

Red	24V	-	-	1NO 1NC	GS1 KJRMT-11-24-RT
Green	24V	-	-	1NO 1NC	GS1 KJRMT-11-24-GN
Yellow	24V	-	-	1NO 1NC	GS1 KJRMT-11-24-GB
Blue	24V	-	-	1NO 1NC	GS1 KJRMT-11-24-BL
Clear	24V	-	-	1NO 1NC	GS1 KJRMT-11-24-KL

2NO 2NC Momentary/Spring Return - 24V


Red	24V	-	-	2NO 2NC	GS1 KJRMT-22-24-RT
Green	24V	-	-	2NO 2NC	GS1 KJRMT-22-24-GN
Yellow	24V	-	-	2NO 2NC	GS1 KJRMT-22-24-GB
Blue	24V	-	-	2NO 2NC	GS1 KJRMT-22-24-BL
Clear	24V	-	-	2NO 2NC	GS1 KJRMT-22-24-KL

Illuminated Pushbutton_KJRMT (Silver Bezel)



IP65



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Maintained/Latching - 24V

Red	24V	1NO	-	-	GS1 KJRMT-10Z-24-RT
Green	24V	1NO	-	-	GS1 KJRMT-10Z-24-GN
Yellow	24V	1NO	-	-	GS1 KJRMT-10Z-24-GB
Blue	24V	1NO	-	-	GS1 KJRMT-10Z-24-BL
Clear	24V	1NO	-	-	GS1 KJRMT-10Z-24-KL

1NC Maintained/Latching - 24V

Red	24V	-	1NC	-	GS1 KJRMT-01Z-24-RT
Green	24V	-	1NC	-	GS1 KJRMT-01Z-24-GN
Yellow	24V	-	1NC	-	GS1 KJRMT-01Z-24-GB
Blue	24V	-	1NC	-	GS1 KJRMT-01Z-24-BL
Clear	24V	-	1NC	-	GS1 KJRMT-01Z-24-KL

1NO 1NC Maintained/Latching - 24V

Red	24V	-	-	1NO 1NC	GS1 KJRMT-11Z-24-RT
Green	24V	-	-	1NO 1NC	GS1 KJRMT-11Z-24-GN
Yellow	24V	-	-	1NO 1NC	GS1 KJRMT-11Z-24-GB
Blue	24V	-	-	1NO 1NC	GS1 KJRMT-11Z-24-BL
Clear	24V	-	-	1NO 1NC	GS1 KJRMT-11Z-24-KL

2NO 2NC Maintained/Latching - 24V


Red	24V	-	-	2NO 2NC	GS1 KJRMT-22Z-24-RT
Green	24V	-	-	2NO 2NC	GS1 KJRMT-22Z-24-GN
Yellow	24V	-	-	2NO 2NC	GS1 KJRMT-22Z-24-GB
Blue	24V	-	-	2NO 2NC	GS1 KJRMT-22Z-24-BL
Clear	24V	-	-	2NO 2NC	GS1 KJRMT-22Z-24-KL

Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration		Part Number
--------------	-------------	--------------	--------------------------------	--	-------------



Illuminated Pushbutton_KJRM T (Silver Bezel)



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Momentary/Spring Return - 230V

Red	230V	1NO	-	-	GS1 KJRM T-10-220-RT
Green	230V	1NO	-	-	GS1 KJRM T-10-220-GN
Yellow	230V	1NO	-	-	GS1 KJRM T-10-220-GB
Blue	230V	1NO	-	-	GS1 KJRM T-10-220-BL
Clear	230V	1NO	-	-	GS1 KJRM T-10-220-KL

1NC Momentary/Spring Return - 230V

Red	230V	-	1NC	-	GS1 KJRM T-01-220-RT
Green	230V	-	1NC	-	GS1 KJRM T-01-220-GN
Yellow	230V	-	1NC	-	GS1 KJRM T-01-220-GB
Blue	230V	-	1NC	-	GS1 KJRM T-01-220-BL
Clear	230V	-	1NC	-	GS1 KJRM T-01-220-KL

1NO 1NC Momentary/Spring Return - 230V

Red	230V	-	-	1NO 1NC	GS1 KJRM T-11-220-RT
Green	230V	-	-	1NO 1NC	GS1 KJRM T-11-220-GN
Yellow	230V	-	-	1NO 1NC	GS1 KJRM T-11-220-GB
Blue	230V	-	-	1NO 1NC	GS1 KJRM T-11-220-BL
Clear	230V	-	-	1NO 1NC	GS1 KJRM T-11-220-KL


2NO 2NC Momentary/Spring Return - 230V

Red	230V	-	-	2NO 2NC	GS1 KJRM T-22-220-RT
Green	230V	-	-	2NO 2NC	GS1 KJRM T-22-220-GN
Yellow	230V	-	-	2NO 2NC	GS1 KJRM T-22-220-GB
Blue	230V	-	-	2NO 2NC	GS1 KJRM T-22-220-BL
Clear	230V	-	-	2NO 2NC	GS1 KJRM T-22-220-KL



Illuminated Pushbutton_KJRM T (Silver Bezel)



Dimensional Drawing:



Cut-out Hole Drawing:



1NO Maintained/Latching - 230V

Red	230V	1NO	-	-	GS1 KJRM T-10Z-220-RT
Green	230V	1NO	-	-	GS1 KJRM T-10Z-220-GN
Yellow	230V	1NO	-	-	GS1 KJRM T-10Z-220-GB
Blue	230V	1NO	-	-	GS1 KJRM T-10Z-220-BL
Clear	230V	1NO	-	-	GS1 KJRM T-10Z-220-KL

1NC Maintained/Latching - 230V

Red	230V	-	1NC	-	GS1 KJRM T-01Z-220-RT
Green	230V	-	1NC	-	GS1 KJRM T-01Z-220-GN
Yellow	230V	-	1NC	-	GS1 KJRM T-01Z-220-GB
Blue	230V	-	1NC	-	GS1 KJRM T-01Z-220-BL
Clear	230V	-	1NC	-	GS1 KJRM T-01Z-220-KL

1NO 1NC Maintained/Latching - 230V

Red	230V	-	-	1NO 1NC	GS1 KJRM T-11Z-220-RT
Green	230V	-	-	1NO 1NC	GS1 KJRM T-11Z-220-GN
Yellow	230V	-	-	1NO 1NC	GS1 KJRM T-11Z-220-GB
Blue	230V	-	-	1NO 1NC	GS1 KJRM T-11Z-220-BL
Clear	230V	-	-	1NO 1NC	GS1 KJRM T-11Z-220-KL

2NO 2NC Maintained/Latching - 230V

Red	230V	-	-	2NO 2NC	GS1 KJRM T-22Z-220-RT
Green	230V	-	-	2NO 2NC	GS1 KJRM T-22Z-220-GN
Yellow	230V	-	-	2NO 2NC	GS1 KJRM T-22Z-220-GB
Blue	230V	-	-	2NO 2NC	GS1 KJRM T-22Z-220-BL
Clear	230V	-	-	2NO 2NC	GS1 KJRM T-22Z-220-KL

IP65

Dimensional Drawing:

Cut-out Hole Drawing:

24V

Red	24V	-	-	-	GS1 KJRMN-24-RT
Green	24V	-	-	-	GS1 KJRMN-24-GN
Yellow	24V	-	-	-	GS1 KJRMN-24-GB
Blue	24V	-	-	-	GS1 KJRMN-24-BL
Clear	24V	-	-	-	GS1 KJRMN-24-KL

230V

Red	230V	-	-	-	GS1 KJRMN-220-RT
Green	230V	-	-	-	GS1 KJRMN-220-GN
Yellow	230V	-	-	-	GS1 KJRMN-220-GB
Blue	230V	-	-	-	GS1 KJRMN-220-BL
Clear	230V	-	-	-	GS1 KJRMN-220-KL

Technical Specification

General Data:

Front Dimensions:	Ø 36 mm	Max. Storage Temperature:	-50°C ... 85°C
Panel Cut -out:	Ø 30.5 mm	Max. Operating Temperature:	-50°C ... 85°C, without illumination
Front Bezel Height:	2.7 mm		-30°C ... 65°C, using LEDs
Operating Travel:	6 mm	Mechanical Life:	1 m switching cycles
IP Rating:	IP67	Electrical Life:	1 m operations at rated load
Illumination:	Yes	Contact Resistance NO:	<20 mOhm
Contact Type:	Mod ular Contact Block	Contact Resistance NC:	<20 mOhm
Protection Class:	II (protective insulation)	Min. Current:	1 mA
Connection Type:	Screw Conne ction 2 x 2.5 mm²	Min. Voltage:	5V
Contact Material:	AgNi		

	Alternate Current	Direct Current
Rated Insulation Voltage:	600V	600V
Rated Operating Voltage:	240V / 440V	440V / 250V / 125V / 60V / 24V
Rated Operating Current:	3A / 1.6A	0.12A / 0.2A / 0.4A / 1A / 2A

Approvals:



Use & Applications:

- ✓ The actuators are designed for exclusive applications as well as use in harsh environments.
- ✓ Flexible contact configuration and ease of assembly.
- ✓ The units can be used in every field of application.
- ✓ The control units are designed to accept a clearly visible marking, easy to produce and comprising a variety fo symbols and inscriptions.
- ✓ Multiple standards nameplates are available and also according to user's requirements.