


Illustration	Colour	Possible Contact Configuration	Part Number
--------------	--------	--------------------------------	-------------

Emergency Stop_RRJUV



Turn to Reset: 1NO Momentary

Red (Mushroom head)	1NO	-	-	GS1 RRJUV-01-RT
---------------------	-----	---	---	-----------------



Turn to Reset: 2NO Momentary

Red (Mushroom head)	-	2NO	-	GS1 RRJUV-02-RT
---------------------	---	-----	---	-----------------


Turn to Reset: 1NO 1NC Momentary

Red (Mushroom head)	-	-	1NO 1NC	GS1 RRJUV-11-RT
---------------------	---	---	---------	-----------------

Dimensional Drawing:



Cut-out Hole Drawing:



Awards:



Technical Specification

General Data:

Front Dimensions:	Ø 28 mm	Max. Storage Temperature:	-50°C ... 85°C
Panel Cut-out:	Ø 22.3 mm	Max. Operating Temperature:	-50°C ... 85°C, without illumination
Front Bezel Height:	2 mm		-30°C ... 65°C, using LEDs
Operating Travel:	3 mm	Mechanical Life:	1 m switching cycles
IP Rating:	IP66, IP67, IP69K	Electrical Life:	1 m operations at rated load
Illumination:	No	Contact Resistance NO:	<20 mOhm
Contact Type:	Twin contact block. Separate plungers, positive opening contact	Contact Resistance NC:	<20 mOhm
Protection Class:	II (protective insulation)	Min. Current:	1 mA
Connection Type:	Screw Connection	Min. Voltage:	5V
Contact Material:	AgNi		

	Alternate Current	Direct Current
Rated Insulation Voltage:	250V	300V
Rated Operating Voltage:	250V	250V / 125V / 60V / 24V
Rated Operating Current:	1.5A	0.2A / 0.4A / 1A / 2A

Approvals:



Use & Applications:

- ✓ The actuators are designed for exclusive applications as well as use in harsh environments.
- ✓ Flexible contact configuration and ease of assembly.
- ✓ The units can be used in every field of application.
- ✓ The control units are designed to accept a clearly visible marking, easy to produce and comprising a variety of symbols and inscriptions.
- ✓ Multiple standards nameplates are available and also according to user's requirements.