



solution control system

บริษัท ชเลเกิ้ล อิเล็กโตรคอนแทค (ไทยแลนด์) จำกัด



(Managing Director)
Mr. Banhan Sangfasuwan
คุณ บรรหาร สังข์ฟ้าสุวรรณ

081-904-9749

02-889-3747-8

095-249-8798

slgthailand.com

mr.banhan888@gmail.com

schlegelthaiweb@gmail.com

66/36 หมู่ 4 ต.ศาลายา อ.พุทธมณฑล จ.นครปฐม 73170
66/36 Moo 4, Salaya, Phutthamonthon
Nakhonpathom 73170

Product Overview



Fascinating Electrotechnics

Control Units



RVA

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 12 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



EMERGENCY STOPS

* with safety Contact Blocks

Modern and attractive designs combine with mechanical robustness and outstanding functionality.

Panel cut-outs: Ø 16 mm, 22 mm, 30 mm
Degree of protection: IP65/IP66/IP67/IP69K



KOMBITAST-R-JUWEL

Front dimensions: Ø 36 mm
Panel cut-out: Ø 30.5 mm
Front bezel height: 2.7 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II
* tested down to -40°F/-40°C



ENCLOSURES

Offer enough space inside to safeguard control units and terminal blocks at its optimum.

Available in various types:

- Equipped Stainless Steel Enclosures
- Insulated Plastic Enclosures
- Equipped Insulated Plastic Enclosures
- Compact enclosure for profile rail or wall mounting (minibox)



OKTRON-JUWEL

Front dimensions: 25 x 25 mm
Panel cut-out: 23.1 x 23.1 mm
Front bezel height: 2 mm
Travel: 3 mm
Degree of protection: IP65
Protection class: II



LIMIT SWITCH

Degree of protection: IP65
Operating temperatures: 25°C to 55°C
Max. rated current / AC: 6A
Rated frequency: 50 to 60Hz
Max. rated voltage: AC 380V, DC 220V



QUARTRON-JUWEL

Front dimensions: 27 x 27 mm
Panel cut-out: 24 x 24 mm
Front bezel height: 2.5 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



PEDAL SWITCHES

Pedal switches are used wherever manual operation is not possible. Robust light metal casing, resistance capacity, extreme durability and mechanical stability distinguish our pedal switches.

Degree of protection: IP65
Protection class: II



QUARTEX-R-JUWEL

Front dimensions: 30 x 30 mm
Panel cut-out: 26 x 26 mm
Front bezel height: 6 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



PANEL MOUNT JACKS

Front dimensions: Ø 28mm, Ø 30mm, 25 x 25mm,
Panel cut-out: Ø 22.3 mm, 23 x 23mm
Front bezel height: 2 mm
Travel: 3 mm



VANDALISM PROOF

Front dimensions: Ø 28 mm/27 x 27mm
Panel cut-out: Ø 22.3mm/24 x 24mm
Front bezel height: 2.3 mm/1.4 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



CONTACT BLOCKS

Contact configuration: 1NC 1NO,
2NC 2NO
Rating voltage: 250V~, 20mV to 48V AC/DC
Connection type: Screw connection, Faston terminals/





OKTRON

Front dimensions: 25 x 25 mm
Panel cut-out: Ø 16.2 mm
Front bezel height: 7.5 mm
Travel: 3 mm
Degree of protection: IP65
Protection class: II



SHORTRON (base-plate mounting)

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 2 mm
Travel: 2.3 mm/1.8 mm
Degree of protection: IP65/IP67
Protection class: II



OKTRON-R

Front dimensions: Ø 25 mm
Panel cut-out: Ø 16.2 mm
Front bezel height: 7 mm
Travel: 3 mm
Degree of protection: IP65
Protection class: II



RX-JUWEL

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 2.6 mm
Travel: 3 mm
Degree of protection: IP65
Protection class: II



QUARTRON QUARTRON_MOSAIC

Front dimensions: 25 x 25 mm
* for mosaic on request 24 x 24 mm
Panel cut-out: Ø 16.2 mm
Front bezel height: 12 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



RONDEX

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 12 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



RONTRON-R-JUWEL

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 2 mm
Travel: 3 mm
Degree of protection: IP65
Protection class: II



RONDEX-M

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 12 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



RONTRON-Q-JUWEL

Front dimensions: 28 x 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 2 mm
Travel: 3 mm
Degree of protection: IP65
Protection class: II



DUX-Basic

Front dimensions: Ø 30 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 12 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II



SHORTRON

Front dimensions: Ø 28 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 2 mm
Travel: 2.3 mm/1.8 mm
Degree of protection: IP65/IP67
Protection class: II



QUARTEX-R

Front dimensions: 30 x 30 mm
Panel cut-out: Ø 22.3 mm
Front bezel height: 12 mm
Travel: 6 mm
Degree of protection: IP65
Protection class: II